

## KPM862

### RFID ticket printer for OEM integration

KPM862 is the ultra-compact, flexible and sturdy top-of-the-range ticket printer.

Thanks to the adjustable paper guides (ticket width from 40 to 86mm) KPM862 is extremely versatile.

It is available in 2 versions: with dual feeder, thanks to which it is possible to manage 2 different types of paper and with Veriprint, a patented Custom system that can instantly check the readability of the data (e.g. barcode) during the ticket printing phase and thus avoids the issue of tickets with dubious validity. KPM862 can be equipped with original CUSTOM HF / UHF RFID antennas, an exclusive CIS sensor, with whom you can read any type of ticket and ensure the alignment. Ideal for modern kiosks with a slim design, less moving parts (cost reduction) and full ticket scanning.




#### ACCESSORIES

- Custom made RFID HF / UHF
- Front ejector to ensure that the ticket falls inside the kiosk
- Selector + ejector to divert the ticket into a special compartment of the kiosk, ideal for RFID applications
- Barcode stock control activation license

## TECHNICAL SHEET

<b>Printing Method</b>	Thermal with fixed head
Number of dots	8 dots/mm
Resolution	203 dpi
Printing (mm/sec)	220 mm/sec (high speed)
Character set	PC437, PC850, PC860, PC863, PC865, PC858
Supported Barcode	1D and 2D: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, AZTEC, QRCODE, GS1 Databar
Printing Format	Height/Width from 1 to 8, bold, reverse, underlined, italic
Printing Direction	Normal, 90°, 180°, 270°
Paper width	from 40 mm to 86 mm
Paper weight	from 70 to 255 g/m <sup>2</sup>
Paper thickness	max 280 $\mu$ m
Roll Dimension	max 300 mm
Sensors	CIS for notch/gap detection and "stock control" reading
Emulation	Cupps compliant native AEA 2012 support
Interfaces	RS232 / USB / Ethernet
Flash Memory	2 MB internal + 8 MB external
RAM Memory	640 KB internal + 8 MB external
Drivers	Self-installing Printer Driver - Win7, 8, 8.1, 10 (32 - 64 bit compatible). WHQL certified (only on request). Self-installing USB Virtual RS232 Driver - Win7, 8, 8.1, 10 (32 - 64 bit compatible). WHQL certified (only on request); Linux 32-64 bit compatible; Android, iOS, Windows Phone
Software Tools	PrinterSet, Custom Power Tool
Power supply	24 Vdc $\pm$ 10%
Medium consumption	1.12 A (12,5% dots turned on)
Head Life	100Km / 100M pulses
MCBF	1.500.000 cuts
Operating temperature	-20°C + 60°C
Dimensions	163.8(L) x 96.5(H) x 152.5(W) mm (standard model) 182.9(L) x 96.5(H) x 152.5(W) mm (model with ejector) 241.6(L) x 96.5(H) x 152.5(W) mm (model with selector) 240.9(L) x 96.5(H) x 155.5(W) mm (model with dual feeder) 260(L) x 96.5(H) x 155.5(W) mm (model with dual feeder + ejector) 318.7(L) x 96.5(H) x 155.5(W) mm (model with dual feeder + selector)

## MODELS



## 915LK010100700

PRINTER KPM862 ETH USB RS232




## 915LK010200700

PRINTER KPM862 ETH USB  
RS232 DF



## 915LK030100700

PRINTER KPM862 ETH uSB RS232  
VERIPRINT



## 915LK010500700

PRINTER KPM862 ETH USB RS232  
RFID HF

---

CUSTOM S.P.A. - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 29 April 2021