

W22IB3S-SPA369

21.5" Intel® Celeron® N2930 IP69K Stainless PCAP Chassis Panel PC



KEY FEATURES

- 21.5", 1920 x 1080 ,P-cap touch with flat design
- Intel® Celeron® Bay Trail-M N2930, 1.83 GHz
- SUS 316 / AISI 316 stainless steel for food and chemical industries
- Full IP69K waterproof enclosure
- A true flat, easy-to-clean front surface with edge-to-edge design
- Plenty of I/Os, including USB 2.0, RS232 and RJ45-10/100/1000 LAN
- Waterproof ports with adapter cables for external connectivity
- Support VESA/ YOKE mount
- Support Glove/ Rain mode
- Optical bonding (optional)




SPECIFICATIONS

| Display | | | | |
|----------------------------|---|------------------------------|---|----------------|
| Resolution | 1920x1080 | Size | 21.5 inches | |
| Contrast Ratio | 3000:1 | Panel Brightness | 250 nits | |
| View Angles | 89,89,89,89 | Active Area | 476.64x268.11 mm | |
| Touch / Glass | Projected Capacitive Multi Touch Screen | | | |
| System Specification | | | | |
| Processor | Intel Celeron N2930 1.83GHz (up to 2.16GHz) | Memory | 1 x SO-DIMM, DDR3L 1600 MHz, 4GB 8GB (Optional) | |
| Storage | 1 x mSATA SSD 128GB. mSATA SSD up to 512GB. (Optional) | Ethernet controller | 2 x Intel® Ethernet Controller | |
| Operating System | Windows 10 IoT Enterprise (64 bit) (Optional) Linux Ubuntu 20.04 (Optional) | WLAN | Support (Optional) | |
| BT | Support (Optional) | | | |
| Mechanical | | | | |
| Dimension | 541 x 337 x 56.2 mm | Mounting | VESA Mount Yoke Mount | |
| Enclosure | Stainless Housing | | Cooling System | Fanless design |
| Environment | | | | |
| Operating Humidity | 10% to 90% RH, Non-Condensing | Operating Temperature | 0°C to 45°C | |
| Storage Temperature | -20°C to 60°C | IP rating | IP69K | |
| Certification | | | | |
| Certification | CE, FCC | | | |
| IO Ports | | | | |
| Power Input | 1 x M12 waterproof connector for 12V DC | USB Port | 1x M12 waterproof connector for 2 x USB2.0 | |
| Serial Port | 1 x M12 waterproof connector for RS232 | LAN | 1 x waterproof Giga LAN RJ45 connector | |
| Indicator | 1 x LED Indicator for power 1 x LED Indicator for storage | | | |

| | |
|---------------------|---|
| Control | |
| Button | 1 x Power Button 1 x Reset Button |
| Accessory | |
| Accessory | 100~240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector External COM cable with waterproof connector External LAN cable with waterproof connector Waterproof caps VESA screws |
| Power | |
| Power Rating | 12V DC (M12 type) |

DIMENSIONS UNIT:MM



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
3. All specifications are subject to change without prior notice.